


FlexiLed Lighting – Data Sheet

Voltage	Power consumption per Metre	LEDs per Section	LEDs per Metre	Cutting interval (approx) Cm	Max working length from one connector (Metres)
LED Colour: Red / YellowGreen / Amber					
12	2.16	5	36	14	15
24	2.16	10	36	28	30
110	5.50	18	36	50	160
230	5.75	36	36	100	320
LED Colour: White / Blue / Pure Green					
12	3.00	3	36	8	15
24	3.00	6	36	17	30
110	5.50	18	36	50	160
230	5.75	36	36	100	320

Accessories:



Inline Connection



Power Lead Connection



Power Lead c/w Rectifier

- BFMN - Male connector
- BFFN - Female connector
- BFMV - Power leads
- CRPV - Power leads with in-line rectifier
- BFSN - In line connector set
- Caps - For cut ends

Mechanical Details: Extruded Flexible Flame Retardant PVC Housing (12x6) or (8x5).

Approvals :

CE
 EN60598-1:1993 and hence LVD Directives 72/23/EEC & 93/68/EEC
 EM55015:2001 EN61000-3-2:2001 EN61000-3-3:1995 and hence EMC Directives 92/31/EEC

International Components Hixon Industrial Estate Hixon Staffordshire ST18 0PY
 Tel: 01889 271135 Fax: 01889 271183